

Start Highbay

START Highbay IP65 1-10V 26000lm 865 WB

0039352



Product features

- START Highbay, includes 1 m cables, black aluminium housing, 26,000 Lm, 200 W, 130 Lm/W, 6500 K, drive current: 5000 mA, CRI 80, 90° beam angle, 1-10 V dimmable, IP65, IK08, 54,000 hrs (L80/B50), (D x H) 339 x 194 mm, 1 m mains cable, 1 m control cable, 1.2 m chain length including hooks



PRODUCT OVERVIEW

Product name	START Highbay IP65 1-10V 26000lm 865 WB
Technology	LED
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC001716
E-number FI	4306967
E-number SE	7214421
Warranty	5 years
Fixture luminous flux (lm)	26000
Luminaire efficacy (lm/W)	130
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	90
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	200
Electrical protection	Class I
Control gear type	Other
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Black
IP rating	IP65
IK rating	IK08
Product EAN number	5410288393520

DATA TABLE

Start Highbay

START Highbay IP65 1-10V 26000lm 865 WB

0039352

General data

Product name	START Highbay IP65 1-10V 26000lm 865 WB
Technology	LED
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-30°C - 50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001716
E-number FI	4306967
E-number SE	7214421
Warranty	5 years

Optical data

Fixture luminous flux (lm)	26000
Luminaire efficacy (lm/W)	130
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	90
Distribution type	Direct
Glare control	< 25
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	200
Mains voltage (V)	230V~
Lamp power factor	0.95
Electrical protection	Class I
Control gear type	Other
Dimmable	Yes
Minimum dimming level (%)	1
Drive current (mA)	5000
Inrush Current (A)	60
Inrush Duration (µs)	300
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	6
Max. Luminaires per 13A C Breaker	8
Max. Luminaires per 16A C Breaker	9
Max. Luminaires per 20A C Breaker	10
Max. Luminaires per 10A B Breaker	3
Max. Luminaires per 13A B Breaker	4
Max. Luminaires per 16A B Breaker	5
Max. Luminaires per 20A B Breaker	7

Start Highbay

START Highbay IP65 1-10V 26000lm 865 WB
0039352

Lifetime data

Lifespan L70 B50	54000
Lifespan L80 B50	54000
Lifespan L90 B50	54000
Lifespan L90 B10	50000

Physical data

Housing colour	Black
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	339
Nominal Product Width (mm)	339
Nominal Product Height (mm)	194
Nominal Product Diameter (mm)	339
Weight (kg)	3.7



Packaging

Single packaging type	Carton
Product EAN number	5410288393520
Packaging single length / height (cm)	40.0
Packaging single width (cm)	40.0
Packaging single depth (cm)	18.7
DUN14 (outer)	05410288393520
Units per outer package	1
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	40.0
Packaging outer depth (cm)	18.7







Safety data

Optimal operating condition (°C)	-30-50
----------------------------------	--------


PHOTOMETRY



Start Highbay START Highbay IP65 1-10V 26000lm 865 WB 0039352




TECHNICAL DRAWINGS




Start Highbay


START Highbay IP65 1-10V 26000lm 865 WB
0039352


SYLVANIA 0039352


 This luminaire contains built-in LED lamps

 } LED


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built-in LED lamps

 } LED

The lamps cannot be changed in the luminaire.

SYLVANIA 0039352 

874/2012