

AUXILIARY CONTACT BLOCK WITHOUT POSITION  
INDICATION FOR PLUGGING ONTO CONTACTORS 1NO



### General technical data:

<b>product brand name</b>		SIRIUS
<b>Acceptability for application</b>		Contact relay and power contactor
<b>Protection class IP / on the front</b>		IP20
<b>Ambient temperature</b>		
• during storage	°C	-55 ... +80
• during operating	°C	-25 ... +55
<b>Mechanical operating cycles as operating time</b>		
• typical		10,000,000
<b>Insulation voltage / with degree of pollution 3</b>		
• rated value	V	690
<b>Impulse voltage resistance</b>		
• rated value	kV	6

### Auxiliary circuit:

<b>Number of NC contacts / for auxiliary contacts</b>		
• instantaneous switching		0
• lagging switching		0
<b>Number of NO contacts / for auxiliary contacts</b>		
• instantaneous switching		1
• leading switching		0

<b>Operating current / of the auxiliary contacts / at AC-12</b>		
• at 24 V	A	10
• at 230 V	A	10
• maximum	A	10
<b>Operating current</b>		
• of the auxiliary contacts		
• at AC-14		
• at 125 V	A	10
• at AC-15		
• at 24 V	A	10
• at 230 V	A	5.6
• at 400 V	A	3.6
• at AC-15 / at 690 V	A	2.3
<b>Operating current</b>		
• of the auxiliary contacts / at DC-13		
• at 24 V	A	10
• at 60 V	A	5
• at 110 V	A	1.14
• at 220 V	A	0.48

#### Installation/ mounting/ dimensions:

<b>Mounting type</b>		snap-on mounting
<b>Width</b>	mm	12
<b>Height</b>	mm	70
<b>Depth</b>	mm	51.5







#### Connections/ terminals:

<b>Type of the connectable conductor cross-section</b>		
• for auxiliary contacts		
• finely stranded		
• with conductor end processing		2x (0.5 ... 1.0 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )
• for AWG conductors / for auxiliary contacts		2x (18 ... 12)

#### Safety:

<b>Product function / positively driven operation to IEC 60947-5-1</b>		Yes
--	--	-----

#### Certificates/ approvals:

General Product Approval		Test Certificates	
 		<a href="#">other</a>	
Shipping Approval			other
			 <a href="#">Confirmation</a> <a href="#">Declaration of Conformity</a>
Further information:			
<b>Information- and Downloadcenter (Catalogs, Brochures,...)</b> <a href="http://www.siemens.com/industrial-controls/catalogs">http://www.siemens.com/industrial-controls/catalogs</a>			
<b>Industry Mall (Online ordering system)</b> <a href="http://www.siemens.com/industrial-controls/mall">http://www.siemens.com/industrial-controls/mall</a>			
<b>Cax online generator</b> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>			
<b>Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)</b> <a href="http://support.automation.siemens.com/WW/view/en/3TX4010-2A/all">http://support.automation.siemens.com/WW/view/en/3TX4010-2A/all</a>			
<b>Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)</b> <a href="http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TX4010-2A">http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TX4010-2A</a>			

last change:

Apr 21, 2014