

ISOLATOR 40A TRIPLE POLE+NEUTRAL



Figure similar

Model		
product brand name		SETRON
Product designation		On/Off switches
Type of light source		Not applicable
Mounting type / for light source		Not applicable
Design of the switching function		Switch disconnecter
General technical data		
Number of poles		3
Number of poles / Note		3P+N
Short-circuit current rating	kA	10
Type of voltage		AC
Protection class		
Protection class IP		Other
Switching capacity		
Switching capacity current / Rated value	kA	0.12
Main circuit		
Operating voltage / Rated value	V	440
Operating current / Rated value	A	40
Appearance		
Color / of the lens		Not applicable
Product details		
Product component / Signal lamp		No

Product function

Product function / positive opening (acc. to DIN VDE 0113)		No
--	--	----

Number

Number of NC contacts		0
Number of NO contacts		3
Number of CO contacts		0

Mechanical Design

Installation depth	mm	70
Number of width units		4

General Product Approval



[other](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TL16400>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5TL16400/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TL16400

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

05.05.2015