



EAN: 5607353112715

Emb.: 1

Peso Líquido: 1kg

CARACTERÍSTICAS GERAIS

Complies with EN 61439-3

For flush mounting

Made from thermoplastic

Color: white RAL 9010

2 rows, 28 modules

Opaque door, door with reversible frame

Installation of equipment on DIN rail (35 mm) EN50022. Distance between rails 150mm

Mechanical characteristics: polystyrene material

Insulation voltage 400V

Maximum humidity (50%HR at + 40°C)

Class II insulation

IP41/IK07

Halogen-free

Accessories included:

Equipped with T/N connector - Ref: SL7N8N16T

Circuit identification label

Option:

Gray color RAL 7035

Fixconnect quick connector

CARACTERÍSTICAS TÉCNICAS

Brand	TEV
Icons	
Cor	No
EF000003 - Mounting method	Flush mounted (plaster)
EF000266 - Number of rows	2
EF002950 - Width in number of modular spacings	28
EF000339 - Type of cover	Door
EF009212 - Cover model	Closed
EF006244 - Transparent cover/door	false
EF001596 - Material housing	Plastic
EF000040 - Height	514 mm
EF000008 - Width	358 mm
EF000049 - Depth	94 mm
EF000218 - Built-in depth	89 mm
EF015776 - Earthing terminal block	true
EF015777 - Neutral terminal block	true
EF001134 - DIN-rail	true
EF000118 - With mounting plate	false
EF000007 - Colour	White
EF000116 - RAL-number	9010
EF005474 - Degree of protection (IP)	IP41
EF006306 - With lock	false
EF004462 - Type of closure	Cylinder