



E2E-X2B1T8-M5

Sensor de proximidad, inductivo, cuerpo corto de SUS, M8, apantallado, 2 mm, cc, 3 hilos, PNP NA, IO-Link COM3, conector
M8 de 3 contactos

Especificações

Size	M8
Mounting type	Flush
Sensing distance	2 mm
Overall length of sensor	39 mm
Thread length	22 mm
Material housing	Stainless steel
Output type	IO-Link, PNP
Operation mode	NO
Connection method	Connector M8 - 3 pin
Cable specifications	-
IO-Link function	✓
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP69K

Produtos relacionados



Conjuntos de cabos e conectores M8

Conjuntos de cabos e conectores industriais para qualquer aplicação

Livraria CAD



E2E NEXT Datasheet

EN PDF 40 MB



E2E(Q) - Basic Models Lista remissiva

EN PDF 700 KB



E2E(Q) - Premium Models Lista remissiva

EN PDF 700 KB



E2E[Q]-XxBxxxx Ficheiro IO-Link IODD

EN ZIP 1 MB



EAC Mark removal Aviso de descontinuação

EN PDF 200 KB



IO-Link Series Brochura

PT PDF 2 MB