

TECHNICAL INFORMATION

PAINEL ENCASTRAR QUADRADO 6W 4000K BRANCO

Panel de Encastrar e Superfície, ideal para tectos falsos com altura limitada.

Recessed and Surface Panel, ideal for dropped ceiling with limited height.

Panel de Encastrar y Superficie, ideal para techos falsos con altura limitada.


ILAR-00068



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Led Type	SMD	Lenght	120mm	Total Luminous Flux	505lm
Mounting Type	Recessed	Width	120mm	Luminous Efficacy	85lm/w
Body Material	Aluminium	Height	9mm	Beam Angle	120°
Housing Colour	White	Weight	0.16kg	Colour Temperature	4000K
Body Shape	Square	Cut-Out	105x105mm	Colour Rendering Index	>80
LGP	PS			Colour Consistency	<= 6
Nominal Lifetime (EOL end of life)	25000hrs			UGR	
LED Brand	Samsung LED				
Useful Lifetime Based on LM70	-				
Dimmable	No				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	6W	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	85-265V	Energy Consumption KWH/1000H	6kwh	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP44	ROHS	YES
Power Factor	0.5	Protection Class	II	Warranty	2 YEARS
Operating Temperature	- 20° C to + 40° C	Protection Class IK (shock resistance)	-		

SIZE



Designed by Aron Light in Portugal. Made in PRC

