

Socket 2P+T 10/16A 250 Vac - shielded tulip contacts

BT-N4180 | EAN. 8012199016399



Product Line

Livinglight, BTicino

DESCRIPTION

Socket 2P+T 10/16A 250 Vac - centre distance 19mm and 26mm - shielded tulip contacts - white

TECHNICAL CHARACTERISTICS

Model	Italian type Bipasso	Concurrently switching neutral conductor	No
Protective contact	Round	Number of active contacts (round)	4
Number of active contacts (flat)	0	Number of active contacts (square)	0
Assembly arrangement	Basic element with central cover plate	With complementary luminous signal	No
Number of ports USB-A	0	Number of empty module positions	0
Number of socket outlets	1	Socket outlets phase-separated	No
Number of modules (module system)	1	Number of socket outlets switchable	0
Number of phases	1	Imprint/indication	None
Connection type	Screwed terminal	With hinged lid	No
With enhanced contact protection	Yes	Label space/information surface	No
Colour	White	RAL-number (similar)	9016
Metallic colour	No	Transparent	No
Lockable	No	Eject-mechanism	No
Insulated mounting	No	With function lighting	No
With orientation lighting	No	Overvoltage protection	No
Fault current protection	No	With miniature fuse	No
Special power supply	None	Mounting method	Flush-mounted

Type of fastening	Snap mounting (engagement)	Material	Plastic
Material quality	Thermoplastic	Halogen free	Yes
Surface protection	Untreated	Surface finishing	Matt
Antimicrobial treatment	No	With loop through function	Yes
With on/off switch	No	Colour of switch operator	White
Rotated central insert	No	Nominal current	16 A
Nominal voltage	250 V	Frequency (Min-Max)	50-60 Hz
Suitable for degree of protection (IP)	IP20	degree of impact strength (IK)	IK00
Device width	22 mm	Device height	44 mm
Device depth	37 mm	Min. depth of built-in installation box	36 mm
Compatible with Apple HomeKit	No	Compatible with Amazon Alexa	No
Compatible with Google Assistant	No	IFTTT support available	No
With Wi-Fi signal repeater	No	With built-in bluetooth speaker	No
For heavy conditions according to VDE	No	Built-in depth	26 mm
Operating / setting temperature (Min-Max)	-5-35 °C	Storage temperature (Min-Max)	-5-35 °C
Voltage type	AC	Power Delivery	No
Cable nature for connection	Flexible or rigid	Cable section (Min-Max)	2.5-2.5 mm ²
Cable support	Other	Connected object	No

DOCUMENTATION

Agreements & specifications

PEP-EPD	LGRP-00165-V02.01-EN	PDF (803 KB)
---------	----------------------	--------------

Catalogue pages & other

Catalog Commercial Page	CAT-LL-2M	PDF (39.5 MB)
Catalog Commercial Page	CAT-LL-3M	PDF (38.7 MB)

Technical documentation

Technical Sheet	F01684EN/00	PDF (2.3 MB)
-----------------	-------------	--------------